

Part No.	Forward current(mA)	Power dissipation(W)	Emitting Color	Dominant Wavelength (nm) TC(%)	Luminous Intensity (LM)		Forward Voltage(V)	
					Min.	Typ.	Typ.	Max.
RC-P30RCA0-XX	2000	27	Red	620-630	800	1500	12.0	15.0
RC-P30YCA0-XX	2000	27	Yellow	585-595	800	1500	12.0	15.0
RC-P30BCA0-XX	1600	30	Blue	460-470	250	450	17.0	22.0
RC-P30GCA0-XX	1600	30	Green	520-530	800	1500	17.0	22.0
RC-P30WCA0-XX	1600	30	White	6000-7000	1000	1500	17.0	22.0
RC-P30WCA0-XX	1600	30	Warm white	2700-3300	600	1200	17.0	22.0
RC-P50RCA0-XX	4000	44	Red	620-630	1500	2000	10.0	12.0
RC-P50YCA0-XX	4000	44	Yellow	585-595	1500	2000	10.0	13.0
RC-P50BCA0-XX	3200	50	Blue	460-470	500	1500	15.0	18.0
RC-P50GCA0-XX	3200	50	Green	520-530	1500	2000	15.0	18.0
RC-P50WCA0-XX	3200	50	White	6000-7000	2000	2500	15.0	18.0
RC-P50WCA0-XX	3200	50	Warm white	2700-3300	1500	2000	15.0	18.0

**Outline Dimension(mm)**

